



Model 型号	S-50-5/24	
	S-50-5	S-50-24
直流电压DC voltage	5V	24V
电流范围 current range	0~10A	0~2.1A
额定电流Rated current	10A	2.1A
额定功率Rated Power	50W	50W
纹波与噪声Ripple and Noise	80mVp-p	120mVp-p
电压调整范围 (SVR1) Voltage adjustment range (SVR1)	4.5~6.7V	25.8~32.7V
电压精度Voltage Accuracy	+/-1%~2%	
线性调整率Line regulation	+/-0.5%	
负载调整率Load Regulation	+/-1%	
启动、上升时间 Setup rise hold up time	1000ms,30ms/230VAC 2000ms,30ms/115VAC at full load	
保持时间retention time	30ms/230VAC 12ms/115VAC at full load	
电压范围current range	85~264VAC 110/220VAC	
效率efficiency	83%	89%
浪涌电流surge current	冷启动45A/230VAC	
漏电流leak current	<0.75mA/240VAC	
过负载excess load	额定输出功率的110~150% 保护模式：打嗝模式，异常条件移除后自动回复	
过电流 overcurrent	5.82~7.3V	28.2~33V
	保护模式：关断输出电压，重启回复	
工作温度operating temperature	-30~+70°C	
工作湿度Operating humidity	20~90%RH,无冷凝	
储存温度、湿度 Storage Temp. & Hum	-40~+85°C, 10~95%RH	
温度系数 temperature coefficient	+/-0.03%/°C (0~50°C)	
耐振动vibration resistance	10~500Hz,5G 10min/cycle	
尺寸size	L160 x W97x H42mm	
包装packing	纸盒 60pcs/CTN	
重量weigh	0.354kg	