

图片			
	Model 型号	S-100-5	
		S-100-5	
输出	直流电压DC voltage	5V	
	电流范围 current range	0~20A	
	额定电流Rated current	20A	
	额定功率Rated Power	100W	
	纹波与噪声Ripple and Noise	120mVp-p	
	电压调整范围 (SVR1) Voltage adjustment range (SVR1)	4.8~6.7V	
	电压精度Voltage Accuracy	+/-1%~2%	
	线性调整率Line regulation	+/-0.5%	
	负载调整率Load Regulation	+/-1%	
	启动、上升时间 Setup rise hold up time	1000ms,30ms/230VAC 1000ms,30ms/115VAC at full load	
输入	保持时间retention time	55ms/230VAC 12ms/115VAC at full load	
	电压范围current range	85~264VAC 110/220VAC (可承受300VAC浪涌输入5	
	效率efficiency	88%	
	浪涌电流surge current	冷启动45A/230VAC	
保护	漏电流leak current	<0.75mA/240VAC	
	过负载excess load	额定输出功率的110~150% 保护模式：打嗝模式，异常条件移除后自动回复	
	过电压 overcurrent	6.6~8.2V	
		保护模式：关断输出电压，重启回复	
环境	工作温度operating temperature	-30~+70°C	
	工作湿度Operating humidity	20~90%RH,无冷凝	
	储存温度、湿度 Storage Temp. & Hum.	-40~+85°C, 10~95%RH	
	温度系数 temperature coefficient	+/-0.03%/°C (0~50°C)	
	耐振动vibration resistance	10~500Hz,5G 10min/cycle X,Y,Z 60min	
其他	尺寸size	L198 x W98 x H42mm	
	包装packing	纸盒 50pcs/CTN	
	重量weigh	0.512kg	