

|    |   |  |  |
|----|---|--|--|
| 图片 |  |  |  |
|    | Model 型号  | S-60-12  |  |
|    |   | S-60-12  |  |
| 输出 | 直流电压DC voltage  | 12V  |  |
|    | 电流范围 current range  | 0~5A   |  |
|    | 额定电流Rated current   | 5A   |  |
|    | 额定功率Rated Power   | 60W  |  |
|    | 纹波与噪声Ripple and Noise   | 80mVp-p  |  |
|    | 电压调整范围 (SVR1)<br>Voltage adjustment range (SVR1)                                  | 11.2~12.9V   |  |
|    | 电压精度Voltage Accuracy  | +/-1%~2%   |  |
|    | 线性调整率Line regulation  | +/-0.5%  |  |
|    | 负载调整率Load Regulation  | +/-1%  |  |
|    | 启动、上升时间<br>Setup rise hold up time  | 1000ms,30ms/230VAC 2000ms,30ms/115VAC at full load |  |
|    | 保持时间retention time  | 30ms/230VAC 12ms/115VAC at full load               |  |
| 输入 | 电压范围current range   | 85~264VAC 110/220VAC                               |  |
|    | 效率efficiency  | 86%  |  |
|    | 浪涌电流surge current   | 冷启动45A/230VAC                                      |  |
|    | 漏电流leak current   | <0.75mA/240VAC                                     |  |
| 保护 | 过负载excess load  | 额定输出功率的110~150%                                    |  |
|    |   | 保护模式：打嗝模式，异常条件移除后自动回复                              |  |
|    | 过电流 overcurrent   | 73.2~17.2V   |  |
|    |   | 保护模式：关断输出电压，重启回复                                   |  |
| 环境 | 工作温度operating temperature   | -30~+70°C  |  |
|    | 工作湿度Operating humidity  | 20~90%RH,无冷凝                                       |  |
|    | 储存温度、湿度<br>Storage Temp. & Hum.   | -40~+85°C, 10~95%RH                                |  |
|    | 温度系数 temperature coefficient  | +/-0.03%/°C (0~50°C)                               |  |
|    | 耐振动vibration resistance   | 10~500Hz,5G 10min/cycle                            |  |
| 其他 | 尺寸size  | L160 x W97x H42mm                                  |  |
|    | 包装packing   | 纸盒 60pcs/CTN                                       |  |
|    | 重量weigh   | 0.354kg  |  |