



Model 型号	S-150-12	
	S-150-12	
直流电压DC voltage	12V	
电流范围 current range	0~12.5A	
额定电流Rated current	12.5A	
额定功率Rated Power	150W	
纹波与噪声Ripple and Noise	100mVp-p	
电压调整范围 (SVR1) Voltage adjustment range (SVR1)	14.3~18.9V	
电压精度Voltage Accuracy	+/-1%~2%	
线性调整率Line regulation	+/-0.5%	
负载调整率Load Regulation	+/-1%	
启动、上升时间 Setup rise hold up time	500ms,30ms/230VAC 500ms,30ms/115VAC at full load	
保持时间retention time	40ms/230VAC 35ms/115VAC at full load	
电压范围current range	85~264VAC 110/220VAC (可承受300VAC浪涌输入5	
效率efficiency	88%	
浪涌电流surge current	冷启动60A/230VAC	
漏电流leak current	<0.75mA/240VAC	
过负载excess load	额定输出功率的110~140% 保护模式：打嗝模式，异常条件移除后自动回复	
过电流 overcurrent	13.2~17.2V	
	保护模式：关断输出电压，重启回复	
工作温度operating temperature	-30~+70 °C	
工作湿度Operating humidity	20~90%RH,无冷凝	
储存温度、湿度 Storage Temp. & Hum.	-40~+85 °C, 10~95%RH	
温度系数 temperature coefficient	+/-0.03%/°C (0~50 °C)	
耐振动vibration resistance	10~500Hz,5G 10min/cycle X,Y,Z 60min	
尺寸size		
包装packing		
重量weigh		