



| | | | |
|--|--|------------|--|
| Model 型号 | S-240-12/24 | | |
| | S-240-12 | S-240-24 | |
| 直流电压DC voltage | 12V | 24V | |
| 电流范围 current range | 0~20A | 0~10A | |
| 额定电流Rated current | 15A | 10A | |
| 额定功率Rated Power | 240W | 240W | |
| 纹波与噪声Ripple and Noise | 150mVp-p | 200mVp-p | |
| 电压调整范围 (SVR1) Voltage adjustment range (SVR1) | 14.3~18.9V | 28~32V | |
| 电压精度Voltage Accuracy | +/-3%~4% | | |
| 线性调整率Line regulation | +/-0.5% | | |
| 负载调整率Load Regulation | +/-2.5% | | |
| 启动、上升时间 Setup rise hold up time | 1300ms,50ms/230VAC 1300ms,50ms/115VAC at full load | | |
| 保持时间retention time | 16ms/230VAC 12ms/115VAC at full load | | |
| 电压范围current range | 90~264VAC 110/220VAC (可承受300VAC浪涌输入5 | | |
| 效率efficiency | 88% | 87% | |
| 浪涌电流surge current | 冷启动60A/230VAC | | |
| 漏电流leak current | <2mA/240VAC | | |
| 过负载excess load | 额定输出功率的110~140% 保护模式：打嗝模式，异常条件移除后自动回复 | | |
| 过电流 overcurrent | 13.2~17.2V | 28.8~36.6V | |
| | 保护模式：关断输出电压，重启回复 | | |
| 工作温度operating temperature | -30~+70 °C | | |
| 工作湿度Operating humidity | 20~90%RH,无冷凝 | | |
| 储存温度、湿度 Storage Temp. & Hum. | -40~+85 °C, 10~95%RH | | |
| 温度系数 temperature coefficient | +/-0.03%/°C (0~50 °C) | | |
| 耐振动vibration resistance | 10~500Hz,5G 10min/cycle X,Y,Z 60min | | |
| 尺寸size | L200 x W110 x H50mm | | |
| 包装packing | 纸盒 36pcs/CTN | | |
| 重量weigh | 0.825kg | | |