



Model 型号	S-360-12/24		
	S-360-12	S-360-24	
直流电压DC voltage	12V	24V	
电流范围 current range	0~30A	0~15A	
额定电流Rated current	30A	15A	
额定功率Rated Power	360W	360W	
纹波与噪声Ripple and Noise	200mVp-p	300mVp-p	
电压调整范围 (SVR1) Voltage adjustment range (SVR1)	14.3~18.9V	28~32V	
电压精度Voltage Accuracy	+/-3%~4%		
线性调整率Line regulation	+/-1.5%		
负载调整率Load Regulation	+/-1.5%		
启动、上升时间 Setup rise hold up time	1300ms,50ms/230VAC 1300ms,50ms/115VAC at full load		
保持时间retention time	16ms/230VAC 12ms/115VAC at full load		
电压范围current range	90~264VAC 110/220VAC (可承受300VAC浪涌输入5		
效率efficiency	81%	80%	
浪涌电流surge current	冷启动60A/230VAC		
漏电流leak current	<2mA/240VAC		
过负载excess load	额定输出功率的110~140% 保护模式：打嗝模式，异常条件移除后自动回复		
过电流 overcurrent	13.2~17.2V	28.8~36.6V	
	保护模式：关断输出电压，重启回复		
工作温度operating temperature	-30~+70 °C		
工作湿度Operating humidity	20~90%RH,无冷凝		
储存温度、湿度 Storage Temp. & Hum.	-40~+85 °C, 10~95%RH		
温度系数 temperature coefficient	+/-0.03%/°C (0~50 °C)		
耐振动vibration resistance	10~500Hz,5G 10min/cycle X,Y,Z 60min		
尺寸size	L200 x W110 x H50mm		
包装packing	纸盒 36pcs/CTN		
重量weigh	0.825kg		