


图片				
	Model 型号	S-480-12		
输出		S-480-12		
	直流电压DC voltage	12V		
	电流范围 current range	0~40A		
	额定电流Rated current	40A		
	额定功率Rated Power	480W		
	纹波与噪声Ripple and Noise	200mVp-p		
	电压调整范围 (SVR1) Voltage adjustment range (SVR1)	14.3~18.9V		
	电压精度Voltage Accuracy	+/-3%~4%		
	线性调整率Line regulation	+/-1.5%		
	负载调整率Load Regulation	+/-1.5%		
	启动、上升时间 Setup rise hold up time	1500ms,50ms/230VAC 1500ms,50ms/115VAC at full load		
	保持时间retention time	23ms/230VAC 23ms/115VAC at full load		
输入	电压范围current range	90~264VAC 110/220VAC (可承受300VAC浪涌输入5		
	效率efficiency	81%		
	浪涌电流surge current	冷启动60A/230VAC		
	漏电流leak current	<2mA/240VAC		
保护	过负载excess load	额定输出功率的110~140% 保护模式：打嗝模式，异常条件移除后自动回复		
	过电流 overcurrent	13.2~17.2V		
		保护模式：关断输出电压，重启回复		
环境	工作温度operating temperature	-30~+70℃		
	工作湿度Operating humidity	20~90%RH,无冷凝		
	储存温度、湿度 Storage Temp. & Hum	-40~+85℃, 10~95%RH		
	温度系数 temperature coefficient	+/-0.03%/℃ (0~50℃)		
	耐振动vibration resistance	10~500Hz,5G 10min/cycle X,Y,Z 60min		
其他	尺寸size	L215 x W115 x H50mm		
	包装packing	纸盒 21pcs/CTN		
	重量weigh	0.955kg		