



型号 model
输出功率 output power
输出电压 output volt
输出电压容差 Output voltage tolerance
额定输出电流 output current
输出电流范围 Output current range
纹波及噪音 mVp-p
负载稳定度 Load regulation
效率 efficiency
输入电压范围 input voltage range
输入电流 input current
冲击电流 surge current
漏电流 leak current
过载保护 overload protection
温度系数 temperature coefficient
抗震性能 anti-seismic property
耐压性能 pressure-resistant properties
隔离电阻 isolation resistance
工作温度 operating temperature
存储温度 storage temperature
外观尺寸 size
认证 identification



12V2A

24W

12VDC

± 1%

2.0A

0~2.0A

120mVp-p

± 0.5%

85%

100~240VAC

0.3A

cold boot current 18A/110V 36A/240V

<1mA/240VAC

105%~200%

± 0.03% °C (0~50°C)

10~500Hz, 2G 10min./1term, time60min, each axle

input/output time: 1.5KVAC input and shell: 1.5KVAC
input/output shell: 0.5KVAC

input/output, input and shell, : 500VDC/100MΩ

-10°C~45°C, 20%~90%RH

-20°C~85°C, 10%~95%RH

L81.7mm*W48.6mm*H33mm

CE ROHS