

	
型号 model	12V1A
输出功率 output power	12W
输出电压 output volt	12VDC
输出电压容差 Output voltage tolerance	±1%
额定输出电流 output current	1A
输出电流范围 Output current range	0~1.0A
纹波及噪音 mVp-p	120mVp-p
负载稳定度 Load regulation	±0.5%
效率 efficiency	85%
输入电压范围 input voltage range	100~240VAC
输入电流 input current	0.06~0.13A
冲击电流 surge current	cold boot current 18A/110V 36A/240V
漏电流 leak current	<1mA/240VAC
过载保护 overload protection	105%~200%
温度系数 temperature coefficient	±0.03%°C (0~50°C)
抗震性能 anti-seismic property	10~500Hz, 2G 10min./1term, time60min, each axle
耐压性能 pressure-resistant properties	input/output time: 1.5KVAC input and shell: 1.5KVAC input/output shell: 0.5KVAC
隔离电阻 isolation resistance	input/output, input and shell, : 500VDC/100MΩ
工作温度 operating temperature	-10°C~45°C, 20%~90%RH
存储温度 storage temperature	-20°C~85°C, 10%~95%RH
外观尺寸 size	L75 x W40x H47mm 0.085kg
认证 identification	CE ROHS
