



| |
|---------------------------------------|
| 型号 model |
| 输出功率 output power |
| 输出电压 output volt |
| 输出电压容差 Output voltage tolerance |
| 额定输出电流 output current |
| 输出电流范围 Output current range |
| 纹波及噪音 mVp-p |
| 负载稳定度 Load regulation |
| 效率 efficiency |
| 输入电压范围 input voltage range |
| 输入电流 input current |
| 冲击电流 surge current |
| 漏电流 leak current |
| 过载保护 overload protection |
| 温度系数 temperature coefficient |
| 抗震性能 anti-seismic property |
| 耐压性能 pressure-resistant properties |
| 隔离电阻 isolation resistance |
| 工作温度 operating temperature |
| 存储温度 storage temperature |
| 外观尺寸 size |
| 认证 identification |



12V5A

60W

12VDC

$\pm 1\%$

5A

0-5.0A

120mVp-p

$\pm 0.5\%$

85%

100-240VAC

0.3~0.65A

cold boot current 18A/110V 36A/240V

<1mA/240VAC

105%~200%

$\pm 0.03\%^\circ\text{C}$ (0~50 $^\circ\text{C}$)

10~500Hz, 2G 10min./1term, time60min, each axle

input/output time: 3KVAC input and shell: 3KVAC
input/output shell: 0.5KVAC

input/output, input and shell, : 500VDC/100M Ω

-10 $^\circ\text{C}$ ~45 $^\circ\text{C}$, 20%~90%RH

-20 $^\circ\text{C}$ ~85 $^\circ\text{C}$, 10%~95%RH

L132 x W58 x H34mm 0.24kg

CE ROHS