



型号 model
输出功率 output power
输出电压 output volt
输出电压容差 Output voltage tolerance
额定输出电流 output current
输出电流范围 Output current range
纹波及噪音 mVp-p
负载稳定度 Load regulation
效率 efficiency
输入电压范围 input voltage range
输入电流 input current
冲击电流 surge current
漏电流 leak current
过载保护 overload protection
温度系数 temperature coefficient
抗震性能 anti-seismic property
耐压性能 pressure-resistant properties
隔离电阻 isolation resistance
工作温度 operating temperature
存储温度 storage temperature
外观尺寸 size
认证 identification



12V12.5A

150W

12VDC

$\pm 1\%$

12.5A

0-12.5A

120mVp-p

$\pm 0.5\%$

85%

100-240VAC

1.2~1.4A

cold boot current 18A/110V 36A/240V

<1mA/240VAC

105%~200%

$\pm 0.03\%^\circ\text{C}$  (0~50 $^\circ\text{C}$ )

10~500Hz, 2G 10min./1term, time60min, each axle

input/output time: 6KVAC input and shell: 6KVAC  
input/output shell: 0.5KVAC

input/output, input and shell, : 500VDC/100M $\Omega$

-10 $^\circ\text{C}$ ~45 $^\circ\text{C}$ , 20%~90%RH

-20 $^\circ\text{C}$ ~85 $^\circ\text{C}$ , 10%~95%RH

L163 x W65 x H38mm 0.565kg

CE ROHS